

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 August 2005 (04.08.2005)

PCT

(10) International Publication Number
WO 2005/070771 A1

(51) International Patent Classification⁷: **B65D 1/02**,
55/08, B29C 45/00

(21) International Application Number:
PCT/ZA2004/000162

(22) International Filing Date:
23 December 2004 (23.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004/0618 27 January 2004 (27.01.2004) ZA
2004/1930 10 March 2004 (10.03.2004) ZA
2004/3984 20 May 2004 (20.05.2004) ZA

(71) Applicant and

(72) Inventor: **HUMAN, Jan, Petrus** [ZA/ZA]; 15 Lobelia
Street, 7130 Somersset West (ZA).


(74) Agent: **BACON, Brian**; Brian Bacon & Associates Inc.,
2nd Floor, Mariendahl House, Newlands on Main, Main
Road, 7700 Newlands (ZA).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: TAMPER EVIDENT CLOSURES



(57) Abstract: Preforms (90) from which bottles can be blown are disclosed. Each disclosed preform has a body, a flange (92) encircling the body and a band (94) protruding from the body. The flange (92), the band (94) and the part of the body above the flange (92) define a trough (106). When a cap (102) is fitted, the ring (112) which is joined to the remainder of the cap's skirt along a weakened line (108), as well as the weakened line and the adjacent part of the remainder of the skirt (104), enter the trough. The band (94) can be heat shrunk onto the ring (112).

WO 2005/070771 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*